

Acetate Silk white gloss 110 gsm - Supertack Kraft 135 gsm

Issue: 03/10/2011
Last Modification:
09/03/2022 Revision: 6
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	264 gsm $\pm$ 7%	ISO 536
Total caliper	263 μ m $\pm$ 8%	ISO 534

FACE:

White gloss 100% acetate silk textile

Substance	110 gsm $\pm$ 8	ISO 536
Caliper	120 μ m $\pm$ 14	ISO 534

ADHESIVE

Water emulsion acrylic based supertack type, high initial tack and strong permanent bond for general use. Recommended on a wide variety of substrates, like paper, board, glass, steel

Peel adhesion	16,5N/inch $\pm$ 2	FINAT1
Shear test	4h $\pm$ 2	FINAT8
Quick stick	14,4 N/inch $\pm$ 4	FINAT9
Application temp.	+5°C/+40°C	
Service temp. Range	-20°C/+90°C	

BACKING

One-side coated white kraft, solventless silicon coated		
Substance	135 gsm $\pm$ 7	ISO 536
Caliper	130 μ m $\pm$ 8	ISO 534

SAFETY REGULATIONS.

The adhesive coating complies with FDA 21 CFR 175.105 "adhesives" and meets EN71-3:2018 "Safety of Toys" – Migration of certain elements
The backing paper meets EN71-3:2018 "Safety of Toys" – Migration of certain elements

APPLICATIONS

Prestigious, high quality labels, recommended for the luxury fashion industry. Carpets, shoes and mattresses labels, conference badges, stamps, promotional stickers. Durable and good conformability labels.

Trials are recommended, by the purchaser, prior to use, on the intended substrates, for product suitability.

PRINTABILITY

Face: good results with all conventional printing processes. No thermal transfer printing.

Consult your inks supplier to obtain the best printing results. Backing: good printing results by all common print processes, in one or more colors

ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized
- Release paper certified Forest Stewardship Council® FSC-C107414

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions



ANTALIS.CH

5242 Lupfig, Tel. 056 464 51 11, info.ch@antalis.com

