

MATERIAL DESCRIPTION

Coala Backlit W is a 215 microns translucent polyester film with an outstanding color expression. It is printable with Dye and Pigmented Waterbase inks, and with UV and Latex inks. Coala Backlit W provides a wide color gamut, incredibly vivid colors and deep blacks with an even diffusion of light. Bright and bluish surface for excellent printing quality.

PRINTER & INK COMPATIBILITY



FILM THICKNESS

215
μ

PRODUCT DESCRIPTION

- Thickness: 215 mic
- Grammage 270 g/m² N/A
- Gloss 60°: 3 % ASTM D2457
- Gloss 85°: 5 % ASTM D2457
- Shade (fs) L: 85 ANSI T (D50/2°/Abs/No)
a: 1.0
b: -7.0

PRINTING AND LAMINATING

- Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%
- Use care in handling printed material, surface susceptible to abrasion
- To optimize the printing quality, printer need to be set for highest print quality.
- Lamination is optional. In order to protect the image from physical damage and to decrease image-fading,
- Prints have to be completely dry before undergoing further processing or lamination.

APPLICATIONS

- Lightbox advertising
- Illuminated displays
- Exhibition graphics & signage
- Recommended for cosmetics, fashion, airports and any high end image application

BENEFITS

- Translucent and water-resistant
- High dimensionally stable
- Highest ink limit
- Even light diffusion

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

SHELF LIFE STORAGE AND CONDITIONS



- It is recommended to store in the closed original packing in a cool and dry environment.
- Temperature 10°~25°C, Relative Humidity 50% RH
- Processing: within one year after receipt

