

UPM Raflatac Technical Information

03-04-2020 EN SI

Face	JETLASER
Sales Code	N7
Product	Woodfree machine finished paper.
Use	Designed for multifunctional information labelling, especially developed for inkjet (both single- and multicolour), lasers and photocopiers.

Typical technical values

Substance	70	g/m ²	ISO 536	
Caliper	90	µm	ISO 534	
Tensile strength MD	5.2	kN/m	ISO 1924/1	
Tensile strength CD	2.2	kN/m	ISO 1924/1	
Brightness	98	%	ISO 2470/1	
Roughness	5.0	µm	ISO 8791	PPS 10
Opacity	92	%	ISO 2471	
CIE Whiteness	164	%	ISO 11475	
Stiffness MD	0.28	mNm	ISO/DP 2493	
Stiffness CD	0.10	mNm	ISO/DP 2493	

Printability Suitable for laser and inkjet. Flexography, offset and screenprint. Please note that conventional printing can compromise inkjet and laser overprintability.

Disclaimer The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.