

UPM Raflatac Technical Information

25-04-2020 EN SI

Product	PE CLEAR OFFSET / PERMANENT FILM / WHITE KRAFT 130 / SOLID PRINTED
Sales Code	WF/SP37/35/W1
Product use	Product designed for clear labels in applications where resistance against water, oil and chemicals is important and flexibility is required. Recommended for product labeling.

Typical technical values

Face		PE CLEAR OFFSET	
Product	Transparent, glossy, topcoated microabsorbent polyethylene film		
Substance	94	g/m ²	DIN 53352
Caliper	100	µm	DIN 53370
Tensile strength MD	20	N/mm ²	DIN 53455
Tensile strength CD	19	N/mm ²	DIN 53455
Gloss	30	%	DIN 67530/1
Printability	Offset, flexography, screen and letterpress. Special inks designed for non-absorbent materials should be used. Thermal transfer with selected ribbons.		
Additional info sheets	Labelling temperature: min +10 °C. Service temperature after labelling: -10 - +60 °C.		
Adhesive		SP37	
Type	General purpose permanent for synthetic sheets.		
Composition	Acrylic dispersion.		
Use	Good adhesion properties and heat resistance. Excellent clarity, UV-stability and water resistance.		
Tack min	8	N	FTM 9
Shear min	8	h	FTM 8
PE-looptack min	5	N	modified FTM 9
Limitations	Limited adhesion at low temperatures.		
Backing		WHITE KRAFT 130	
Product	White woodfree kraft backing paper.		
Substance	135	g/m ²	ISO 536
Caliper	134	µm	ISO 534
Tensile strength MD	7,5	kN/m	ISO 1924
Tensile strength CD	3,7	kN/m	ISO 1924
Performance			
Total caliper	254 µm		
Minimum labelling temperature	10 °C		
Service temperature	-20 to 100 °C		

Shelf life From date of manufacture: 24 months, under FINAT defined storage conditions (+20-25°C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

Information

Product availability

Standard range. (Other sizes and/or components available upon request).

STANDARD SHEET SIZE (CM)	50x70 / 100x70
PACKAGING TYPE	Ream wrapped / Bulk

Approvals

Approvals

For further compliance information related to food labeling applications, please contact your local sales representative for a Declaration of Conformance (DoC) document.

Approvals

Toy labeling: This product complies with the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements.

Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

