

UPM Raflatac Technical Information

05-01-2021 EN SI

Adhesive	SR24
Sales Code	SR24
Type	Removable
Composition	Waterborne acrylic
Use	A general purpose removable adhesive designed for sheets laminates. Good long-term removability. Good cohesion and adhesion at difficult substrates.

Typical technical values

Tack min	2	N	FTM 9
Shear min	1	h	FTM 8
Labelling temperature min	5	°C	
Service temperature max	80	°C	

Limitations	Not recommended for labelling PVC or acrylic coated surfaces, long term removability might be restricted.
Approvals	For further compliance information related to food labeling applications, please contact your local sales representative for a Declaration of Conformance (DoC) document.
Disclaimer	The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.